

Tremco Ladder Safety Post

Roof Hatch Fall Protection



FEATURES

- Hot or cold applied
- Hot applied in THERMastic
- EPDM/SBR

BENEFITS

- Versatile application
- Efficient/labor saving application method
- Combines high strength polymer blend with weatherability
- Polymer blend is compatible with asphalt

DESCRIPTION

The Safety Post is designed to extend 42 inches above a landing platform to aid safe ladder access through a roof hatch. The spring assisted telescoping design mounts to the top two rungs of a fixed vertical ladder.

MATERIAL

- 1-1/2 inch by 1-1/2 inch by 1/8 inch high strength square tubing with a pull-up loop provided at the upper end to facilitate raising of post.
- Steel: yellow powder coat paint or hot dip galvanized
 - Stainless Steel: Type 304, mill
 - Aluminum: Mill

BALANCING SPRING

Stainless steel constant force spring

HARDWARE

Type 316 stainless steel

STANDARD MODELS

| MODEL | MATERIAL | FINISH |
|-------|-----------------|---------------------|
| BSPY | Steel | Powder Coat, Yellow |
| BSPG | Steel | Hot Dip Galvanized |
| BSPA | Aluminum | Mill |
| BSPS | Stainless Steel | Mill |



Roofing & Building Maintenance

3735 Green Road
Beachwood, Ohio 44122

220 Wicksteed Avenue
Toronto, Ontario, M4H 1G7

www.tremcoroofing.com

1.800.852.6013

Tremco Roofing and Building Maintenance is part of Tremco Construction Products Group.

Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application. The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.